CHAINWAY®





C75

Mobile Terminal with Printer















IRIS

Bluetooth

PSAM



1D Barcode





2D Barcode











Camera

C75 is a devoted handheld computer that offers mobile printing capabilities. The thermal printer supports various printer engines and prints labels and receipts. Built-in dual slots are for PSAM cards to encrypt data. Portable and durable, this device is the perfect multi-use tool for your advanced data capture and mobility needs in retail, healthcare, parking, etc.





Specification

Physical Chara	octeristics
Dimensions	186.89*83.99*35.04-49.49mm
Weight	507g/17.88oz
Display	5.2" IPS FHD 1920x1080P Corning Gorilla Glass, multi-touch panel, gloves
Touch Panel	and wet hands supported
Power	Main battery: Li-ion, rechargeable, 8000mAh
Expansion Slot	2 PSAM slots at most (ISO7816 protocol), 1 slot for SIM card, 1 slot for SIM or TF card
Interfaces	USB 2.0 Type-C, OTG
Audio	Speaker, 2 microphones
Keypad	3 side keys, 1 power key, numeric keyboard
Sensors	Gravity sensor, light sensor, proximity sensor, vibration motor
Performance	
CPU	Cortex-A53 Quad-core 1.3GHz
RAM+ROM	2GB+16GB
Expansion	Supports up to 32 GB Micro SD card
Developing En	vironment
Operating System	Android 6.0
SDK	Chainway Software Development Kit
Language	Java
Tool	Eclipse / Android Studio
User Environment	
Operating Temp.	-4°F to 122°F / -20°C to 50°C
Storage Temp.	-40°F to 158°F / -40°C to 70°C
Humidity	5%RH - 95%RH non condensing
Drop Specification	Multiple 1.2m/3.9ft drops to the concrete
Communicatio	n
WLAN	IEEE802.11 a/b/g/n, 2.4G/5G dual-band, internal antenna
WLAIN	
WLAN	2G: 850/900/1800/1900MHz
WWAN(Europe)	2G: 850/900/1800/1900MHz 3G: 850/900/1900/2100MHz

	2G: 850/900/1800/1900MHz
WWAN(America) WWAN (China)	3G: 850/900/1700/1900MHz
	4G: B2, B4, B7, B12, B17
	2G: 900/1800MHz
	3G: 900/1900/2000/2100MHz
	4G: TDD-LTE: B38, B39, B40, B41
	FDD-LTE: B1, B3, B5
WWAN (Others)	Depending on the country's ISP
Bluetooth	Bluetooth 4.0, BLE
GNSS	GPS/AGPS, GLONASS, BeiDou; internal antenna
Camera	
Camera	13MP Autofocus with flash
Thermal Printe	r
Rate (mm/s)	85
Image Size (pixel)	384 dots
Paper Width (mm)	58
NFC	
Frequency	13.56MHz
Protocol	ISO14443A/B, ISO15693, NFC-IP1, NFC-IP2, etc.
Chips	M1 card (S50, S70), CPU card, NFC tags, etc.
Range	2-4cm
Barcode Scann	ning (optional)
1D Linear Scanner	Zebra SE965 / Honeywell N4313
1D Symbologies	UPC/EAN, Code128, Code39, Code93, Code11, Interleaved 2 of 5, Discrete 2 of 5, Chinese 2 of 5, Codabar, MSI, RSS, etc.
2D Imager Scanner	Zebra SE4710 /Honeywell N6603
2D Symbologies	PDF417, MicroPDF417, Composite, RSS, TLC-39, Datamatrix, QR code, Micro QR code, Aztec, MaxiCode; Postal Codes: US PostNet, US Plane: UK Postal, Australian Postal, Japan Postal, Dutch Postal (KIX), etc.
Iris (optional)	
Rate	<150ms
Rate Range	<150ms 20-40cm

Accessories





AC Adaptor

 $Notice: Product \ specifications \ are \ subject \ to \ change \ without \ prior \ notice. \ / \ Model: \ C75 \ / \ Update \ Date: \ 2018-05-28$

CHAINWAY®