Smarter... Faster... Higher...

UHF RFID Integrated Reader STA IR101

GENERAL DESCRIPTION

STA IR101 is a high performance UHF RFID integrated reader. It is designed upon fully self-intellectual property. Based on proprietory efficient DSP algorithm, it supports fast tag read/write operation with high identification rate. It can be widely applied in many RFID application systems such as logistics, access control, anti-counterfeit and industrial production process control system



FEATURES

- Self-intellectual property;
- ISO18000-6B, Support ISO18000-6C(EPC C1G2) protocol tag;
- 865~867MHz frequency band(frequency customization optional);
- FHSS or Fix Frequency transmission;
- RF output power up to 30dbm(adjustable);
- Built-in 8dbi antenna with effect distance up to 3m-5m*;
- Support auto-running, interactive and trigger-activating work mode;
- Low power dissipation with single +9 DC power supply;
- Support RS232, RS485, Wiegand TCP IP interface;

CHARACTERISTICS

Absolute Maximum Rating

ITEM	SYMBOL	VALUE	UNIT
Power Supply	VCC	16	V
Operating Temp.	T_{OPR}	-10~+55	$^{\circ}$
Storage Temp.	T_{STR}	-20~+75	$^{\circ}$

Electrical and Mechanical Specification

Under $T_A=25^{\circ}C$, VCC=+9V unless specified

ITEM	SYMBOL	MIN	TYP	MAX	UNIT
Power Supply	VCC	8	9	12	V
Current Dissipation	I_{C}		350	650	mA
Frequency	F_{REQ}	865		867	MHz



STALLION SYSTEMS AND SOLUTIONS PVT. LTD.

Ph: 0484 2314592 Email: marketing@stallionindia.com

Branches: Mumbai | Delhi | Bangalore | Ahmedabad | Hyderabad | Chennai | Kolkatta | Kochi Pune | Silvasa | Chandigarh | Trivandrum | Alleppey | Thrissur | Calicut | Kannur



www.stallionglobal.com An ISO 9001: 2015 Certified Company

^{*} Effective distance depends on antenna, tag and environment.