

# **DATASHEET**

# **STA Innova Metalic Tag**

Innova Tag is a UHF Gen2 long range passive tag. It is ideal for deployment in rugged and harsh environments and it gives excellent performance on metallic objects & plastic.



### **Electrical Specification**


Air Interface Protocol	ISO/IEC 18000-6C, EPC Global C1G2
Operational Frequency	865 – 868 MHz or 902 – 928 MHz
Chip	Alien Higgs-3
Memory Configuration	EPC-96 bits, extendible to 480bits
	TID – 96 bits unalterable unique
	User memory – 512 bits
	Access password – 32 bits
	Kill password – 32 bits
Read Range*	On metal – Up to 15 m
	Off metal – Up to 8 m

## **Physical / Mechanical Specification**

Dimensions	150 x 23 x 18 ± 0.2 mm
Hole Dia	5.0mm
Colour**	Grey
Weight	35 g
Encasement	PC / ABS High Impact
Quality Assurance	100% reader tested

#### **Environmental Resistance**

Operating temperature	-40°C to +85°C
Storage temperature	-40°C to +85°C
Ingress protection rating	IP67
Attachment***	Riveting/Screws/Magnetic/Adhesive
Applicable surface	Metal





#### **Chemical Resistance**


Resistant to continuous exposure to salt water for 2 hours
Resistant to continuous exposure to motor oil for 2 hours
Additionally, abrasion resistant against HCL and IPA

#### **Additional Services**

Pre-encoding	On request
Customization***	Logo / text printing on
Customization	request







#### **Order Information**

Part No.	Description
U0412911-EU	Alien higgs-3 chip tuned at ETSI frequency
U0412911-US	Alien higgs-3 chip tuned at US frequency



#### STALLION SYSTEMS AND SOLUTIONS PVT. LTD.

Ph: 0484 2314592 Email: marketing@stallionindia.com

Branches : Mumbai | Delhi | Bangalore | Ahmedabad | Hyderabad | Chennai | Kolkatta | Kochi Pune | Silvasa | Chandigarh | Trivandrum | Alleppey | Thrissur | Calicut | Kannur



www.stallionglobal.com An ISO 9001: 2015 Certified Company